



30773502



IP55

## Intermediate switch surface-mounted Berker W.1, polar white matt

### Technical features

#### Architecture

Fixing mode surface-mounting

#### Configuration

- ample room for wiring under the bases of the inserts
- intermediate

#### Main electrical features

Nominal voltage 250 V

Rated voltage 250 V AC

#### Electric current

Switching current 10 AX

#### Materials

Colour of design line polar white

Colour white

RAL colour RAL 9010 - Pure white

Material thermoplastic

Surface appearance matt

#### Dimensions

Depth 61,5 mm

Height 76 mm

Width 76 mm

#### Installation, mounting

Installation mode for screw fastening

#### Connection

Type of connection Quickconnect

- with two clip-in places for Wago 2-wire connection terminals in the housing floor
- with Wago clip-in 2-wire connection terminal for wiring
- with plug-in terminals

#### Cable

- with one entry for 2 cables and one entry for cable and tube

#### Equipment

- with full-face sealing on the rear side of housing for cable entry and surface adjustment on the backside

#### Safety

Protection index IP IP55

---

**Use conditions**

---

Operating temperature	-40...30 °C
Storage/transport temperature	-50...50 °C

---

**Identification**

---

Application, usage	Surface-mounted wet-room installation
Main design line	Berker W.1

---

**Instructions**

---

Information text	Pins of quick-release lock made of ZAMAK
------------------	--

---