



47299949

| Architecture | |
|--|------------------------------|
| Design | according to DIN 49 |
| Fixing mode | flush-moun |
| Connectivity | |
| Type of USB port | o |
| Main electrical features | |
| Nominal voltage | 25 |
| Rated voltage | 250 V |
| Frequency | 50 |
| Rated current | 1 |
| Electric current | |
| Rated current | 1 |
| Cover, door | |
| Cover | Full cover p |
| Colour of design line | anthra |
| Colour | anthracite charcoal gr |
| RAL colour | RAL 7021 - Black g |
| Material | thermopla |
| Surface appearance | n |
| Dimensions | |
| Installation depth, flush-mounted boxes | 31 ו |
| Assembling height | 22 1 |
| Installation, mounting | |
| For installation in 1gang wall boxes | according to DIN 4907 |
| Connection | |
| Connection terminals | according to IEC 6088 |
| Connection terminals | according to VDE 0620-1:2021 |
| - with plug-in terminals | |
| Use | |
| Differentiation characteristic 2 - Sales | enhanced contact protect |

Double SCHUKO socket outlet with cover plate enhanced contact protection, Berker S.1, anthracite, matt



Safety

| protection code against mecanical impacts | 05 |
|---|---------------------------------|
| otection index IP | IP20 |
| nanced contact protection | according to IEC 60884-1 |
| nanced contact protection | according to VDE 0620-1:2021-02 |
| Enhanced contact protection | |

Identification

| Main design line | Berker S.1 |
|------------------|------------|
|------------------|------------|